BERMAD Waterworks



Accessories

Large Control Filter

The Large Control Filter is used for filtration of dirty control fluid that might quickly block a smaller filter element. The Large Control Filter increases the reliability of the control valve system and time between maintenance, while minimizing faulty operation.

Technical Data

Filter Element: Disc Type, 60 mesh; 250 µm

Filter types:

Large Control Filter (F)

Extra Large Control Filter (F1)

Pressure Rating:

25 bar; 350 psi (Standard) 40 bar; 600 psi (HP Model) **Max Temperature:** 80°C; 180°F

Ports:


3/8" NPT female 1/2" NPT female



Materials:

| | | Standard | St. St. | Ni-Al-Bronze | Super Duplex | Hastalloy |
|---|----------------|--|-------------|--------------|--------------|-------------|
| 1 | Body | Carbon Steel, Epoxy Coated | St. St. 316 | Ni-Al-Bronze | Super Duplex | Hastalloy |
| 2 | Covers | Brass | St. St. 316 | Ni-Al-Bronze | Super Duplex | Hastalloy |
| 3 | Stem (1) | St. St. 304 | St. St. 316 | Ni-Al-Bronze | Super Duplex | Hastalloy |
| 4 | Nut | St. St. 304 | St. St. 316 | St. St. 316 | St. St. 316 | St. St. 316 |
| 5 | Filter Element | Construction: Polypropylene, Grooved discs: Polyethylene | | | | |
| | Seals (2) | NBR | | | | |

(1) For HP models stem might differ (2) Optional Seals: EPDM and Viton



Type F - 2.7 kg; 6 lbs Type F1- 5.3 kg; 11.7 lbs

